

S12 - S36

Introducing 2 new models with both high dimension and power



S36



S12

SOFTLED NEW MODELS		
Model	S12 VW-C	S36 VW-C
Power to LED	max 650W - DC current to the LED - flicker free	max 1.300W - DC current to the LED - flicker free
LES (Light Emitting Surface)	1.185x200 mm	1.185x750 mm
Rated Voltage & PFC	90-250V 50-60Hz PFC 0.96	
Power consumption	max 725W	max 1.450W
Power Connection	powerCON IN & OUT	
DMX Data link USITT DMX512-A	5-pin XLR for DMX in & out. RDM control. Wireless DMX available on request (TIMO TWO) Use shielded data cables. Do not overload the daisy chain. Up to a maximum of 32 devices can be used on a single DMX chain.	
DMX Channels	8 / 9- 12/13 or 39/40 - DMX chart for details	
LED BOARDS Lifetime	60.000 hours with 70% Lumen Maintenance. The LED BOARDS are tested and certified up to LM80	
CCT	Tunable from 1.750°K to 14.500°K + RGBA color and color correction mode	
CRI / TLCI	>95 / >96	
Protection Type	IP20	
Ambient operating Temperature	-20° C to +40° C (-4° to 104° F)	
Weight of Fixture with yoke (integrated PSU)	With M.O. Yoke 18,7 Kg (41.2 lb) With Lollipop 15,0 Kg (33.1 lb)	M.O. 43,0 Kg (94.8 lb)
Photometrical @3m distance	3200°K 2.861 Lux / 265.8 FC 5600°K 3.333 Lux / 309.6 FC	3200°K 7.567 Lux / 703.0 FC 5600°K 9.289 Lux / 863.0 FC

Technical info are subject to change without notice. Photometrics values could differ up to +/- 5%. All rights reserved